

## NEW CU-660A Hard Glue

### FEATURES:

- Hard styrene acrylic glue for all kinds of cotton fabric, chemical fabric and nonwoven fabric hard coating.
- Coated mesh under oven temperature 135 °C in 2-3 minutes will cure and fix well
- High hardness, excellent fixing performance and durability.

### Product Data:

item	index
Appearance	Milky white Liquid with blue hue
Solid content (wt%)	23.0±1
PH	7.0-9.0
Viscosity (mpa. s)	<100
Mechanical stability (2500rpm, 0.5hr)	Pass
Tg(°C)	67
Particle Size, um	0.1
Ionicity	Anion

### APPLICATION:

- Fiberglass mesh glue
- Immersive coating
- Could be mixed with CUB-510-45 to adjust the coating stiffness.

### PACKAGING & STORAGE

1. Package: 1MT IBC tote or 22.8MT Flexitank.
2. Storage: the product should be kept away from sun light in a cool place; storage temperature is 5-35 °C; storage time of efficacy is 6 months.

### SAFETY INFORMATION

Please refer to product MSDS.

**重要事项：** 以上资料供阁下参考，并不构成本公司承担用户产品质量及施工两责任的法律保证。在首次使用本产品前或原料或施工环境有较大的改变时，用户必须通过试验，制订最为适合的生产方法及控制测试，以确保产品的一致性及品质。在获知哪种应用及环境和生产条件后本公司可提供技术方面的建议。请向本公司代表询问上述细则。