

# 浙江科力森化学有限公司 Zhejiang Cothanes Chemical Co., Ltd.

地址: 浙江省绍兴市上虞区杭州湾上虞经济技术开发区纬七路12号 电话: 0575-82560088 82050581 传真: 0575-82051479

邮编: 312369 E-mail:zgf@xinlichemical.com Http://www.xinlichemical.com

## **XL-CA Emulsified Asphalt Waterproof Emulsion**

#### 1. Product Introduction

XL-CA is a silicone modified acrylic emulsion, designed to be used for emulsified asphalt waterproof paint.

#### 2. Product Features

XL-CA is an APEO & Formaldehyde free, Enviro friendly water based acrylic emulsion which has good compatibility with Emulsified Asphalt. This emulsion film has excellent adhesive and waterproofing performance.

### 3. Product specification

item	index
Solid content (wt%)	$45.0\pm1$
PH	7. 0-9. 0
Viscosity (mpa. s, 3#30)	2000-6000
Calcium stability	Pass
Mechanical stability (2500rpm, 0. 5hr)	Pass
Minimum film forming temperature(°C)	7
Average particle size ( µ m)	0. 10-0. 20
Surfactant type	Anion

## 4. Package and storage

- 1. Package: 50kg Plastic Drum, 1MT IBC tote.
- 2. Storage: the product should be kept away from the light in a cool place; storage temperature is 5-35 °C; storage time of efficacy is 6 months.

重要事项: 以上资料供阁下参考,并不构成本公司承担用户产品质量及施工两责任的法律保证。在首次使用本产品前或原料或施工环境有较大的改变时,用户必须通过试验,制订最为适合的生产方法及控制测试,以确保产品的一致性及品质。 在获知哪种应用及环境和生产条件后本公司可提供技术方面的建议。请向本公司代表询问上述细则。